

FAMOWOOD SOLVENT MSDS



M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WOOD FILLER SOLVENT

Page: 1

PRODUCT NAME: FAMOWOOD WOOD FILLER SOLVENT
PRODUCT CODE: 37730000

HMIS CODES: H F R P
2*3 0 H

SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ECLECTIC PRODUCTS, INC.
ADDRESS : 1075 ARROWSMITH
EUGENE OR 97402

EMERGENCY PHONE : (800) 535-5053
INFORMATION PHONE : (800) 767-4667
DATE REVISED : 6/20/00
DATE PRINTED : 10/18/05
NAME OF PREPARER : Regulatory Compliance

SECTION 2 - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP), WEIGHT PERCENT. Rows include Acetone, Methyl Ethyl Ketone, and Solvent Naphtha with their respective TLV, PEL, and LD50 values.

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

DOT Classification: Flammable liquid n.o.s. (contains acetone, methyl ethyl ketone), 3, UN 1993, PGII ERG #128
Limited Quantities (0.3 gallon or less): Consumer Commodity ORM-D

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 133 DEG F
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Slower than ether.
APPEARANCE AND ODOR: Colorless, mobile liquid. Hydrocarbon odor.
SPECIFIC GRAVITY (H2O=1): 0.79
MATERIAL VOC: 3.96 lb/gl
SOLUBILITY IN WATER: Appreciable

VOC calculations are based on the federal EPA definition of volatile organic compound under the Clean Air Act. State and local air quality authorities may have more stringent regulation.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

solvents with permanent brain or nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No **IARC MONOGRAPHS:** No **OSHA REGULATED:** No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Persons with severe skin, liver, kidney or lung problems may aggravate these conditions with repeated exposure.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Immediately flush with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention. **SKIN:** Flush skin with water. If irritation occurs, get medical attention. **INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention. **INGESTION:** Do not induce vomiting. Material can be aspirated into lungs, causing chemical pneumonia. Get medical attention immediately. Never give anything by mouth to an unconscious person.

===== SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wear proper protective equipment. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Stop spill at source. Recover liquids for reuse. Soak up remaining residue with absorbent and place in non-leaking containers for proper disposal.

WASTE DISPOSAL METHOD

If product becomes a waste material it would be considered a hazardous waste. Dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep liquid and vapor away from heat, sparks, and flames. Vapors may accumulate and travel to ignition sources distant from handling site. Keep containers closed when not in use. Use with adequate ventilation.

OTHER PRECAUTIONS

Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld, or perform similar operations on or near containers. Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment. Work station conditions should be evaluated by management to determine appropriate personal protection.

===== SECTION 8 - CONTROL MEASURES =====

RESPIRATORY PROTECTION

If exposure may or does exceed occupational exposure limits, use a NIOSH approved respirator to prevent overexposure. In accordance with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors. Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations below recommended levels.

PROTECTIVE GLOVES

Rubber or vinyl-coated gloves are recommended.

M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WOOD FILLER SOLVENT

Page: 4

EYE PROTECTION

Chemical splash goggles and/or full face shield.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

To prevent repeated or prolonged skin contact, wear impervious clothing. Eyewash fountains and safety showers should be easily accessible and ready for use.

WORK/HYGIENIC PRACTICES

Wash thoroughly after handling, and before eating, drinking, or smoking.

===== SECTION 9 - DISCLAIMER =====

To the best of our knowledge, the information provided herein is accurate, obtained from sources believed to be accurate. Since the conditions and methods of use of our product are beyond our control, we disclaim any and all liability arising out of the improper use of this product or the information provided herewith.